

FT Card

668 Barokki primer

Product	Water-based, acrylate primer paint with good filling and sanding properties.
Suitability	Wooden furniture, doors, other wooden structures as well as MDF and fibre board surfaces indoors. Before deployment of the product is recommended to contact the manufacturer in order to ensure the suitability for such use.

Technical data

Dry contents	app. 58% by weight.
Density	app. 1.5 g/ml.
Gloss grade	mat.
Storage	Store in a cool place. Shelf life 36 months. A poorly closed or half-full vessel reduces storage life. Keep from freezing.
Application	Brush, roller or spray gun.
Coverage	8 – 10 m ² /litre on smooth surfaces.
Thinning	Water. Max. 20%.
Drying time	Drying time is dependable on the thickness of the layer, temperature, air humidity and ventilation. - dust dry 30-50 minutes, +23°C - grinding and re-treatable 3-4 hours, +23°C
Cleaning of tools	Warm water and soap.
Tinting	Tintable with standard systems suitable for waterborne system. Not colour accurate.
Packages	0,9, 2,7, 9 and 18 litres.

Instructions for use

Conditions	The surface to be treated must be clean and dry. During work the temperature of air, lacquer and the object must be above +18°C and relative humidity below 70%.
Process	Mix the can well avoiding foam formation. When needed the paint can be diluted with water.
Top coat	670 Barokki furniture paint or 600 Acryline Top.
Environment safety	Product must not be let in sewer system, water systems or in soil. Unused liquid material is to be treated as hazardous waste. Dry, empty cans can be recycled as metal waste. Dry lacquer can be dealt as standard waste.
Safety	Care shall be exercised and unnecessary exposure avoided when using the product. Respiratory protective devices shall be used during spray application. Protective gloves are recommended. A safety data sheet is available.
Flammability	Non-flammable.
EU VOC limit value	(cat A/e) 130g/l (2010). VOC of ready for use product <130g/l.
Transportation	Non ADR classified. Keep from freezing.